Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Product Use: System 90-II Part B System 90-II Part A Hardener

Company Identification

Edison Coatings, Inc. 3 Northwest Drive Plainville, CT 06062

Edison Coatings Tech Info Phone:	1-860-747-2220
Emergency Phone:	1-800-535-5053

2. HAZARDS IDENTIFICATION

Hazard Classification Physical Hazards	Not Classified
Health Hazards	Sensitization, skin
OSHA Defined Hazards	Not Classified

Label Elements Hazard Pictograms



Hazards

May cause skin irritation.

Precautionary Statements

Prevention

Wash thoroughly after handling. Wear protective gloves/clothing/eye protection/face protection.

Response

IF SWALLOWED: Do not induce vomiting. If conscious, have victim drink plenty of water and call a physician immediately.

IF ON SKIN: Wash with soap and water. If skin irritation occurs: Get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

Storage

Store in dry, cool environment.

Disposal

Dispose of contents in accordance with local regulations.

Other Hazards

No data available

3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight%	Chemical Name
1-Chloro-4 (Trifluoromethyl)	<90%	1-Chloro-4 (Trifluoromethyl)
Benzene		Benzene
98-56-6		

4. First Aid Measures

Eye Contact:

Flush eyes with plenty of water for 15 min. while holding eyelids open. Get medical attention.

Skin Contact:

Remove contaminated clothing and wipe excess from skin. Flush skin with water. Cover the affected area with a sterile dressing or clean sheeting and transport for medical care. Control shock, if present. Launder contaminated clothing prior to reuse.

Ingestion:

Do not induce vomiting. Administer 3-4 glasses of milk or water. Get medical attention.

Inhalation:

Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

Medical Conditions Aggravated by Exposure:

Pre-existing eye, skin and respiratory disorders.

5. FIRE FIGHTING MEASURES

Extinguishing Media:

Water spray, Alcohol foam, dry chemical, Carbon Dioxide (CO₂)

Unusual fire and explosion hazards:

May generate toxic or irritating combustion products and carbon monoxide gas. Personnel in vicinity and downwind should be evacuated. At temperatures above 200°F pressure may build in closed containers and explosive rupture is possible.

Fire Fighting Procedures:

Turn off all ignition sources. A face shield should be worn. Firefighters should wear butyl rubber boots, gloves and body suit and self-contained breathing apparatus. Retain expended liquids from firefighting for later disposal.

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Stop the leak/spill, if possible. Ventilate the space involved. Reduce vapor spreading with a water spray. Shut off or remove all ignition sources. Construct a dike to prevent spreading.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep in cool, dry, ventilated storage and in closed containers. Store in steel containers preferably located outdoors, above ground and surrounded by dikes to contain spills or leaks. Do not store in iron or other reactive metal containers.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and Face Protection:

Wear chemical goggles if there is a likelihood of contact with eyes.

Skin Protection:

Wear chemical resistant gloves as required to minimize contact. Wear industry appropriate attire.

Other Personal Protection Data:

Eye wash fountains and safety showers should be available for emergency use. Usual industrial work clothes should be worn.

Respiratory Protection:

Avoid breathing vapor or mists. If exposure may or does exceed occupational exposure limits, use a NIOSH-approved respirator to prevent overexposure.

Ventilation:

Use local exhaust or general dilution ventilation to control exposure within applicable limits.

Exposure Guidelines

There is no data available on either OSHA Permissible Exposure Limits (PEL's) or ACGIH Threshold Limit Value (TLV's) for components of product.

9. PHYSICAL PROPERTIES

Odor: Physical State: pH: Vapor Pressure (mmHg): Vapor Density (Air=1): Boiling Point: Solubility in Water: Coefficient of water/oil distribution: Density (grams per milliliter): Evaporation Rate (Ether=1): Flash Point (Fahrenheit): Flash Point (Celsius): Lower Explosive Limit (%): Upper Explosive Limit (%): Autoignition temperature: Petroleum solvent odor Liquid Not Determined 5.3 (at 70°F) Not Determined >200°F <1.0% Not Determined 1.26 Not Determined >109°F >42°C Not Determined Not Determined Not Determined

10. STABILITY AND REACTIVITY

Stability: Conditions to Avoid: Incompatibility:

Hazardous Polymerization: Hazardous Decomposition Products:

Sensitivity to static discharge:

11. TOXICOLOGICAL INFORMATION

Mutagens/Teratogens/Carcinogens:

This product has no known mutagenic or carcinogenic effects.

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all Federal, State, and Local Regulations.

14. TRANSPORTATION INFORMATION

No information on transportation is available.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

TOXIC SUBSTANCES CONTROL ACT (TSCA) – All components are included in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

OSHA Hazard Communication Standard (29CFR1910.1200) Hazard Class(es) Flammable

EPA SARA TITLE Section 312: Immediate health hazard. Delayed Health Hazard.

Unstable. Polymerization may occur. Heat, open flame Strong oxidizing agents, polymerization initiators, strong acids, strong bases May occur Carbon Monoxide, Carbon Dioxide, Aldehydes, and Acids Not determined.

16. OTHER INFORMATION

Effective Date:	26/Feb/2014
Revision Date:	29/Sep/2017